

C-Print Flock Textile Vinyl

Printable Flock textile vinyl

Description

Heat seal Flock material, specifically formulated for all general Solvent and Eco-Solvent printing and cutting systems.

It features a high covering power, brilliant colour reproduction and an easy handling.

Basic Information

Due to the many different base materials available on the market, the following heat transfer instructions are given as guideline only:

Temperature: 180°C

Time: 15"

Pressure: medium

Application Instructions

- 1) Print and cut the material
- 2) Let the print dry at least 2 hours before rolling, overlaying or heat transferring the material
- 3) Weed the exceeding material
- 4) Remove the image from the backing by hand and over with a silicon treated paper
- 5) Heat apply
- 6) Remove the silicon treated paper

Suitable for

Cotton, polyester, poly-cotton blends and acryl.

Not suitable for treated and dyed garments (sublimation inks)

Washing: (wait 24h after the heat transfer)

60°C Max. – wash inside out - use only mild detergent - no bleach, fabric softener or liquid detergent

Dry-cleaning : not advisable

Tumble drier : yes

N.B. : all information given in this sheet are based on our experience

We recommend to always perform a test before starting standard production

We offer a wide range of **Grafiflex Textile Vinyl's** which enables us to offer something suitable for every budget and application.

Tel: 01827 300500

Free Fax: 0800 318075 Web: www.grafityp.co.uk

E-mail: sales@grafityp.co.uk

GRAFITYP

Siser
THERMO TRANSFER FOR TEXTILES