

C-Print New Textile Vinyl

Thinner printable material

Description

Very thin heat seal material, specifically formulated for ink jet solvent and eco solvent based inks – printing and cutting systems.

Paper backing.

Basic Information

Due to the many different base materials available on the market, the following heat transfer instructions are given as guideline only:

Temperature: 160-165°C

Time: 15"

Pressure: medium

Application Instructions

- 1) Print the material and wait at least 3 minutes before cutting (the dry time is normally settable in automatic mode)
- 2) Cut the material
- 3) Let the print dry at least 12 hours before rolling, overlaying or heat transferring the material
- 4) Weed the exceeding material
- 5) Remove the image from the backing using the **Siser transparent polyester T.T.D.** (adhesive, transparent polyester, resistant to high temperatures) or other application tapes
- 6) Heat apply
- 7) Remove application tape **hot**. Should you use other application tapes, follow the manufacturer's instructions

Suitable for

Cotton, polyester, poly-cotton blends.

Not suitable for treated and dyed garments (sublimation inks)

Washing: (wait 24h after the heat transfer)

50°C Max. – wash inside out - do not use bleach or other aggressive chemical agents

Dry-cleaning : no

Tumble drier : not advisable

N.B. : all information given in this sheet are based on our experience

We offer a wide range of **Grafiflex Textile Vinyl's** which enables us to offer something suitable for every budget and application.

Tel: 01827 300500

Free Fax: 0800 318075 Web: www.grafityp.co.uk

E-mail: sales@grafityp.co.uk

GRAFITYP

Siser
THERMO TRANSFER FOR TEXTILES