

# C-Print Textile Vinyl

*Printable material for application to textiles*

## Description

Heat seal material, specifically formulated for ink jet solvent and eco solvent based inks – printing and cutting systems. The material is very thin, but grants a high covering power.

**Polyester** backing.

## Basic Information

Due to the many different base materials available on the market, the following heat transfer instructions are given as guideline only:

**Temperature:** 150°C

**Time:** 15"

**Pressure:** medium

## Application Instructions

- 1) Print and cut the material
- 2) Let the print dry at least 12 hours before rolling, overlaying or heat transferring the material
- 3) Weed the exceeding material
- 4) Remove the image from the backing using the **Siser transparent polyester T.T.D.** (adhesive, transparent polyester, resistant to high temperatures) or other application tapes
- 5) Heat apply
- 6) Remove application tape **hot**. Should you use other application tapes, follow the manufacturer's instructions

## Suitable for

Cotton, polyester, poly-cotton blends.

Not suitable for treated and dyed garments (sublimation inks)

**Washing:** (wait 24h after the heat transfer)

50°C Max. – wash inside out - do not use bleach or other aggressive chemical agents

**Dry-cleaning :** no

**Tumble drier :** not advisable

*N.B. : all information given in this sheet are based on our experience*

***We recommend to always perform a test before starting standard production***

We offer a wide range of **Grafflex Textile Vinyl's** which enables us to offer something suitable for every budget and application.

**Tel: 01827 300500**

Free Fax: 0800 318075 Web: [www.grafityp.co.uk](http://www.grafityp.co.uk)

E-mail: [sales@grafityp.co.uk](mailto:sales@grafityp.co.uk)

**GRAFITYP**

**Siser**  
THERMO TRANSFER FOR TEXTILES